



CLIP 1100


Triple ply FABRIC DUCTING CLIP HELIX



Applications:

Extraction of extreme hot vapour and fumes.
Oven, steel industry, shipbuilding aircraft, automobile industries

Construction:



- ❶ HT stainless steel mesh
- ❷ Insulating HT glass layer
- ❸ Glass fabric reinforced by woven in stainless steel wire
- ❹ Stainless steel helix

Inside high heat resistant stainless steel mesh
In the middle HT insulating layer
Outside special coated glass fibre fabric, reinforced by woven in stainless steel wire
Reinforced with stainless steel helix clip helix

Proprieties:

Extremely good heat resistant
More mechanical resistance with reinforced fabric with stainless steel wire reinforced fabric
Hardly inflammable
Limited flexing and vibration-resistant

Temperature range:

-120 °C up to + 1100°C
-184 °F up to + 2012°F

Article code:

C3H1100S00ØØLG

*The technical data in this document are given as information, they are our actual knowledge and do not implicate any guarantee of our part.
Users should test the products before installation and using.
These data could be changed with no advices.*



mm	g /m	mm	mm	bar	bar	m
75	1100	3,5	68	-	0,27	2 - 10
80	1200	3,5	72	-	0,23	2 - 10
90	1200	3,5	81	-	0,21	2 - 10
100	1200	3,5	90	-	0,17	2 - 10
110	1300	3,5	99	-	0,14	2 - 10
120	1300	3,5	108	-	0,12	2 - 10
125	1500	3,5	113	-	0,11	2 - 10
130	1500	3,5	117	-	0,10	2 - 10
140	1500	3,5	126	-	0,09	2 - 10
150	1700	3,5	135	-	0,080	2 - 10
160	1700	3,5	144	-	0,070	2 - 10
170	1700	3,5	153	-	0,060	2 - 10
175	2000	3,5	158	-	0,060	2 - 10
180	2000	3,5	162	-	0,050	2 - 10
200	2200	3,5	180	-	0,040	2 - 10
215	2400	3,5	194	-	0,040	2 - 10
225	2700	3,5	203	-	0,040	2 - 10
250	3000	3,5	225	-	0,030	2 - 10
275	3500	3,5	248	-	0,020	2 - 10
300	3900	3,5	270	-	0,020	2 - 10
315	4000	3,5	284	-	0,020	2 - 10
325	4200	3,5	293	-	0,020	2 - 10
350	4600	3,5	315	-	0,020	2 - 10
375	5400	3,5	338	-	0,010	2 - 10
400	5800	3,5	360	-	0,005	2 - 10
450	6700	3,5	405	-	0,009	2 - 10
500	7600	3,5	450	-	0,007	2 - 10
600	9600	3,5	540	-	0,005	2 - 10
700	11100	3,5	630	-	0,004	2 - 10
800	12800	3,5	720	-	0,003	2 - 10
900	14500	3,5	810	-	0,003	2 - 10

Other dimensions between listed are possible on request.

Updated on: 01/05/2018

Technical specifications apply to a temperature of 22°C