



PROSIFLEX
FLEXIBLE HOSE & DUCTING

CLIP 500


HT glass FABRIC DUCTING CLIP HELIX



Applications:

Blowing for heating plants
Chemical industry
Extraction and blowing of hot vapor

Construction:



- ❶ External coated silicone glass fabric
- ❷ Galvanised steel helix

HT silicon external side coated glass fabric
thickness 0,35 mm
Reinforced with galvanised steel
clip helix

Proprieties:

Excellent blower hose
Hardly inflammable
Heat resistant
Very flexible
Limited flexing and vibration-resistant

Compressible: 1 to 6

Temperature range:

-60 °C up to + 500°C
-76 °F up to + 932°F

Article code:

C1HT500S0ØØØLG



mm	g /m	mm	mm	bar	bar	m
50	700	0,35	30	0,90	0,32	2 - 10
60	800	0,35	36	0,78	0,22	2 - 10
65	800	0,35	39	0,68	0,19	2 - 10
70	900	0,35	42	0,67	0,16	2 - 10
75	900	0,35	45	0,62	0,14	2 - 10
80	1000	0,35	48	0,61	0,12	2 - 10
90	1100	0,35	54	0,56	0,1	2 - 10
100	900	0,35	60	0,51	0,08	2 - 10
110	900	0,35	66	0,48	0,06	2 - 10
120	1000	0,35	72	0,33	0,05	2 - 10
125	1000	0,35	75	0,36	0,05	2 - 10
130	1100	0,35	78	0,28	0,04	2 - 10
140	1100	0,35	84	0,25	0,04	2 - 10
150	1200	0,35	90	0,22	0,03	2 - 10
160	1300	0,35	96	0,21	0,03	2 - 10
170	1350	0,35	102	0,19	0,02	2 - 10
175	1400	0,35	105	0,19	0,02	2 - 10
180	1400	0,35	108	0,17	0,02	2 - 10
200	1600	0,35	120	0,15	0,02	2 - 10
215	1700	0,35	129	0,13	0,02	2 - 10
225	1700	0,35	135	0,12	0,01	2 - 10
250	1900	0,35	175	0,1	0,01	2 - 10
275	2100	0,35	193	0,08	0,01	2 - 10
300	2300	0,35	210	0,07	0,009	2 - 10
315	2400	0,35	221	0,06	0,008	2 - 10
325	2500	0,35	228	0,06	0,008	2 - 10
350	2600	0,35	245	0,05	0,007	2 - 10
375	2800	0,35	263	0,05	0,006	2 - 10
400	3000	0,35	280	0,05	0,005	2 - 10
450	3300	0,35	360	0,04	0,004	2 - 10
500	3700	0,35	400	0,04	0,003	2 - 10
600	4400	0,35	480	0,04	0,002	2 - 10
700	5100	0,35	560	0,03	0,002	2 - 10
800	5800	0,35	640	0,02	0,001	2 - 10
900	6500	0,35	720	0,01	0,001	2 - 10

Other dimensions between listed are possible on request.

Updated on: 01/05/2018

Technical specifications apply to a temperature of 22°C

The technical data in this document are given as information, they are our actual knowledge and do not implicate any guarantee of our part.
Users should test the products before installation and using.
These data could be changed with no advices.

PROSIFLEX SAS - 42 Chemin de la Nitrière - 26200 Montélimar - France

SAS au capital de 200.000 € - SIRET 824 546 485 00015 - NAF 2229A - RCS Romans - TVA FR 78 824456485

www.prosiflex.net - contact@prosiflex.net - Tel : +33 (0)4 75 52 56 11