



PROSIFLEX
FLEXIBLE HOSE & DUCTING

CLIP 650


HT glass double ply FABRIC DUCTING CLIP HELIX



Applications:

Extraction of very hot vapor and fumes
Oven, steel industry, shipbuilding
aircraft, automobile industries

Construction:



- ❶❷ Special coated HT glass fabric reinforced by woden in stainless steel wire
- ❸ Galvanised steel helix

Internal and external special coated HT fabric reinforced by woden in stainless steel wire
thickness 0,4 mm
Reinforced with galvanised steel clip helix

Proprieties:

Very good heat resistant
More mechanical resistance with reinforced fabric with stainless steel wire reinforced fabric
Hardly inflammable
Limited flexing and vibration-resistant

Compressible: 1 to 6

Temperature range:

-50 °C up to + 650°C
-58 °F up to + 1202°F

Article code:

C2HT650S00ØØLG



mm	g /m	mm	mm	bar	bar	m
60	1350	0,8	36	-	0,33	2 - 10
65	1450	0,8	39	-	0,31	2 - 10
70	1500	0,8	42	-	0,28	2 - 10
75	1650	0,8	45	-	0,27	2 - 10
80	1800	0,8	48	-	0,23	2 - 10
90	1800	0,8	54	-	0,21	2 - 10
100	1800	0,8	60	-	0,17	2 - 10
110	1900	0,8	66	-	0,14	2 - 10
120	2000	0,8	72	-	0,12	2 - 10
125	2100	0,8	75	-	0,11	2 - 10
130	2100	0,8	78	-	0,1	2 - 10
140	2100	0,8	84	-	0,09	2 - 10
150	2200	0,8	90	-	0,08	2 - 10
160	2400	0,8	96	-	0,07	2 - 10
170	2500	0,8	102	-	0,06	2 - 10
175	2800	0,8	105	-	0,06	2 - 10
180	2800	0,8	108	-	0,05	2 - 10
200	3000	0,8	120	-	0,04	2 - 10
215	3200	0,8	129	-	0,04	2 - 10
225	3400	0,8	135	-	0,04	2 - 10
250	3550	0,8	175	-	0,03	2 - 10
275	4200	0,8	193	-	0,02	2 - 10
300	4400	0,8	210	-	0,02	2 - 10
315	4500	0,8	221	-	0,02	2 - 10
325	4700	0,8	228	-	0,02	2 - 10
350	5000	0,8	245	-	0,02	2 - 10
375	5500	0,8	263	-	0,01	2 - 10
400	5900	0,8	280	-	0,005	2 - 10
450	6700	0,8	360	-	0,009	2 - 10
500	7400	0,8	400	-	0,007	2 - 10
600	9000	0,8	480	-	0,005	2 - 10
700	10100	0,8	560	-	0,004	2 - 10
800	11600	0,8	640	-	0,003	2 - 10
900	13200	0,8	720	-	0,003	2 - 10

Other dimensions between listed are possible on request.

Updated on: 01/05/2018

Technical specifications apply to a temperature of 22°C

The technical data in this document are given as information, they are our actual knowledge and do not implicate any guarantee of our part.
Users should test the products before installation and using.
These data could be changed with no advices.

PROSIFLEX SAS - 42 Chemin de la Nitrière - 26200 Montélimar - France

SAS au capital de 200.000 € - SIRET 824 546 485 00015 - NAF 2229A - RCS Romans - TVA FR 78 824456485

www.prosiflex.net - **contact@prosiflex.net** - **Tel : +33 (0)4 75 52 56 11**