



**PROSIFLEX**  
FLEXIBLE HOSE & DUCTING

## CLIP SILICONE


### Silicone coated glass FABRIC DUCTING CLIP HELIX



#### Applications:

Extraction and blowing of hot vapour  
and exhaust

#### Construction:



- ❶ Silicone-coated-glass fabric
- ❷ Galvanised steel helix

Glass fabric silicone coated wall  
Wall thickness 0,35 mm  
Reinforced with galvanised steel  
clip helix

#### Proprieties:

Hardly inflammable  
Heat resistant  
Good vacuum resistance  
Avoid repeated flexibility uses

Compressible: 1 to 6

#### Temperature range:

-60 °C up to + 300°C  
-140 °F up to + 572°F

#### Article code:

C1SI300S0ØØLG



mm	g /m	mm	mm	bar	bar	m
50	400	0,35	30	0,85	0,32	2 - 10
60	500	0,35	36	0,68	0,22	2 - 10
65	500	0,35	39	0,59	0,19	2 - 10
70	500	0,35	42	0,53	0,16	2 - 10
75	600	0,35	45	0,47	0,14	2 - 10
80	600	0,35	48	0,43	0,12	2 - 10
90	600	0,35	54	0,36	0,1	2 - 10
100	600	0,35	60	0,3	0,08	2 - 10
110	700	0,35	66	0,25	0,06	2 - 10
120	700	0,35	72	0,22	0,05	2 - 10
125	800	0,35	75	0,21	0,05	2 - 10
130	800	0,35	78	0,19	0,04	2 - 10
140	800	0,35	84	0,17	0,04	2 - 10
150	900	0,35	90	0,15	0,03	2 - 10
160	900	0,35	96	0,14	0,03	2 - 10
170	900	0,35	102	0,12	0,02	2 - 10
175	1000	0,35	105	0,12	0,02	2 - 10
180	1000	0,35	108	0,11	0,02	2 - 10
200	1200	0,35	120	0,1	0,02	2 - 10
215	1300	0,35	129	0,09	0,02	2 - 10
225	1400	0,35	135	0,08	0,01	2 - 10
250	1600	0,35	175	0,07	0,01	2 - 10
275	1900	0,35	193	0,06	0,01	2 - 10
300	2100	0,35	210	0,05	0,009	2 - 10
315	2100	0,35	221	0,05	0,008	2 - 10
325	2200	0,35	228	0,05	0,008	2 - 10
350	2500	0,35	245	0,04	0,007	2 - 10
375	2900	0,35	263	0,04	0,006	2 - 10
400	3100	0,35	280	0,03	0,005	2 - 10
450	3600	0,35	360	0,03	0,004	2 - 10
500	4100	0,35	400	0,02	0,003	2 - 10
600	5100	0,35	480	0,02	0,002	2 - 10
700	6000	0,35	560	0,01	0,002	2 - 10
800	6900	0,35	640	0,01	0,001	2 - 10
900	7800	0,35	720	0,01	0,001	2 - 10

Other dimensions between listed are possible on request.

**Technical specifications apply to a temperature of 22°C**

Updated on: 01/05/2018

The technical data in this document are given as information, they are our actual knowledge and do not implicate any guarantee of our part.  
Users should test the products before installation and using.  
These data could be changed with no advices.

**PROSIFLEX SAS - 42 Chemin de la Nitière - 26200 Montélimar - France**

SAS au capital de 200.000 € - SIRET 824 546 485 00015 - NAF 2229A - RCS Romans - TVA FR 78 824456485

**www.prosiflex.net - contact@prosiflex.net - Tel : +33 (0)4 75 52 56 11**